

光滑极限塞规

定制塞规
可定制其它等级, 如H8, H9, G7
可定制直径, 如19.003mm
可定制长度, 如70mm




4124-12C

A型


- 包含通规和止规
- 硬度HRC60±2
- 符合GB/T 1957-2006



B型



A型



B型

H7尺寸公差

(mm)

直径(mm)	Ød1 通规尺寸公差 (mm)	Ød2 止规尺寸公差 (mm)	L1	L2	L	S1, S2
≥2, ≤3	+0.0010/+0.0022	+0.0088/+0.010	6.5	4.5	62	—
>3, ≤6	+0.0013/+0.0027	+0.0106/+0.012	8	6	74	—
>6, ≤10	+0.0015/+0.0033	+0.0132/+0.015	10	7	87	—
>10, ≤14	+0.0018/+0.0038	+0.0160/+0.018	12	8	99	—
>14, ≤18	+0.0018/+0.0038	+0.0160/+0.018	14	10	114	—
>18, ≤24	+0.0023/+0.0046	+0.0186/+0.021	16	12	132	—
>24, ≤30	+0.0023/+0.0046	+0.0186/+0.021	18	14	136	—
>30, ≤40	+0.0023/+0.0055	+0.0220/+0.025	20	15	155	—
>40, ≤50	+0.0023/+0.0055	+0.0220/+0.025	25	18	169	—
>50, ≤65	+0.0028/+0.0064	+0.0264/+0.030	30	18	—	164, 152
>65, ≤80	+0.0028/+0.0064	+0.0264/+0.030	35	25	—	169, 159
>80, ≤100	+0.0032/+0.0075	+0.0308/+0.035	35	25	—	169, 159

H7

型号	直径(mm)	类型
4124-2C	2	A
4124-3C	3	A
4124-4C	4	A
4124-5C	5	A
4124-6C	6	A
4124-7C	7	A
4124-8C	8	A
4124-9C	9	A
4124-10C	10	A
4124-11C	11	A
4124-12C	12	A
4124-13C	13	A
4124-14C	14	A
4124-15C	15	A
4124-16C	16	A

型号	直径(mm)	类型
4124-17C	17	A
4124-18C	18	A
4124-19C	19	A
4124-20C	20	A
4124-21C	21	A
4124-22C	22	A
4124-23C	23	A
4124-24C	24	A
4124-25C	25	A
4124-26C	26	A
4124-27C	27	A
4124-28C	28	A
4124-29C	29	A
4124-30C	30	A
4124-31C	31	A

型号	直径(mm)	类型
4124-32C	32	A
4124-33C	33	A
4124-34C	34	A
4124-35C	35	A
4124-36C	36	A
4124-37C	37	A
4124-38C	38	A
4124-39C	39	A
4124-40C	40	A
4124-41C	41	A
4124-42C	42	A
4124-43C	43	A
4124-44C	44	A
4124-45C	45	A
4124-46C	46	A

型号	直径(mm)	类型
4124-47C	47	A
4124-48C	48	A
4124-49C	49	A
4124-50C	50	A
4124-52C	52	B
4124-55C	55	B
4124-60C	60	B
4124-65C	65	B
4124-70C	70	B
4124-75C	75	B
4124-80C	80	B
4124-85C	85	B
4124-90C	90	B
4124-95C	95	B
4124-100C	100	B

H8

型号	直径(mm)	类型
4124-151C	15	A
4124-221C	22	A

G7

型号	直径(mm)	类型
4124-222C	22	A
4124-282C	28	A