

- 包含通规和止规
- 符合ISO1502标准
- 由含钨工具钢制成, 油淬火, 超低温处理
- 产品的耐磨性好, 寿命长, 尺寸稳定, 光洁度高
- 硬度HRC60-62
- 带生产厂检验证书



4641-6

\*型号说明举例:

公称直径	螺距	等级6H
M1	0.25	-1

型号为**4641-1**

规格(mm)		型号(4641)*		
公称直径	螺距	等级6H	等级6G	等级4H
M1	0.25	-1	—	-1H
M1.1	0.25	-1D1	—	—
M1.2	0.25	-1D2	—	-1D2H
M1.4	0.3	-1D4	—	-1D4H
M1.6	0.35	-1D6	-1D6G	-1D6H
M1.7	0.35	-1D7	—	—
M1.8	0.35	-1D8	-1D8G	-1D8H
M2	0.4	-2	-2G	-2H
M2.2	0.45	-2D2	-2D2G	-2D2H
M2.3	0.4	-2D3	—	—
M2.5	0.45	-2D5	-2D5G	-2D5H
M2.6	0.45	-2D6	—	—
M3	0.5	-3	-3G	-3H
M3.5	0.6	-3D5	-3D5G	-3D5H
M4	0.7	-4	-4G	-4H

规格(mm)		型号(4641)*		
公称直径	螺距	等级6H	等级6G	等级4H
M4.5	0.75	-4D5	-4D5G	—
M5	0.8	-5	-5G	-5H
M6	1	-6	-6G	-6H
M7	1	-7	-7G	-7H
M8	1.25	-8	-8G	-8H
M9	1.25	-9	-9G	—
M10	1.5	-10	-10G	-10H
M11	1.5	-11	-11G	—
M12	1.75	-12	-12G	-12H
M14	2	-14	-14G	-14H
M16	2	-16	-16G	-16H
M18	2.5	-18	-18G	-18H
M20	2.5	-20	-20G	-20H
M22	2.5	-22	-22G	—
M24	3	-24	-24G	—

规格(mm)		型号(4641)*	
公称直径	螺距	等级6H	等级6G
M27	3	-27	-27G
M30	3.5	-30	-30G
M33	3.5	-33	-33G
M36	4	-36	-36G
M39	4	-39	-39G
M42	4.5	-42	—
M45	4.5	-45	—
M48	5	-48	—
M52	5	-52	—
M56	5.5	-56	—
M60	5.5	-60	—
M64	6	-64	—
M68	6	-68	—